


## Product Designation

<b>Product Group:</b>	Polycord round belts
<b>Product Sub-Group:</b>	Polycord round belts
<b>Main Industry Segments:</b>	Applicable in all industry segments
<b>Belt Applications:</b>	General conveying belt; Power transmission belt
<b>Special Features:</b>	Elastic; Flexibility in all directions; Monolithic Belt; Simple and fast joining method
<b>Mode of Use/Conveyance:</b>	Declined; Horizontal; Inclined; Serpentine drives; Twists with short center distance

## Product Design (enlarged)



## Product Construction/Design

<b>1 Friction material:</b>	Thermoplastic polyurethane (TPU)
<b>1 Friction surface structure:</b>	Rough structure
<b>1 Friction cover (Color):</b>	Green (Habasit green)
<b>2 Traction Layer (Material):</b>	Thermoplastic polyurethane (TPU)

## Technical Data

<b>Diameter (d):</b>	5 mm	0.197 in.
<b>Mass of belt (belt weight):</b>	0.024 kg/m	0.0161 lbs./ft.
<b>Pulley diameter (minimum):</b>	50 mm	2 in.
<b>Tensile force for 8% elongation (k8% static) (Habasit standard SOP3-064):</b>	35 N	8 lbf
<b>Nominal peripheral force:</b>	24 N	5 lbs.
<b>Operating temperature admissible (continuous):</b>	Min -20 °C Max 50 °C	Min -4 °F Max 122 °F
<b>Coefficient of friction on steel (roughness CLA max 1.6 micrometer):</b>	0.3	

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554), and are based on the Master Joining Method.

## Additional Technical Information

<b>Chemical Resistance:</b>	Link to 'Chemical resistance information': <a href="http://www.habasit.com/en/chemical-resistance.htm">http://www.habasit.com/en/chemical-resistance.htm</a>  For additional details, please contact your local Habasit representative.
<b>Installation and Handling Instructions:</b>	See Engineering Manual
<b>Limitations:</b>	This product has not been tested according to ATEX standards (atmospheres with explosion risk - ATEX 95 regulation or EU directive 94/9) and therefore is subject to user's analysis in the respective environment.

## Storage

For details consult 'Storage and handling requirements for belts and machine tapes' or contact Habasit. Protect belts from sunlight/UV-radiation/dust and dirt. Store spare belts in a cool and dry place and if possible in their original packaging.

## Legend

*	No calculation Value
2)	Product containing different coating materials such as elastomer, natural fibers, silicones, etc., are not subject to the directive 2002/72/EC
3)	CLA: Coordination of the centre line-average value Ra (in the US also Arithmetical Average (AA)) to the maximum peak to valley height Rt for surfaces manufactured by chip removal.
8)	Due to high coefficient of friction of running/pulley side, the suitability for use on slider beds is limited German federal institute for risk assessment (Bundesinstitut fuer Risikobewertung)
EEC	European Economic Community
EU	European Union (Directive 2002/72/EC)
FDA	Food and Drug Administration
NA	Not available
NAP	Not applicable
USDA	United States Department of Agriculture (Food Safety and Inspection Service, Washington D.C.)

## Disclaimer

### Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products").

SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.